

DATA SHEET FOR  
AUTO-TRANSFORMER # AZ85615


Made for STANDARD

page 1 of 1

LEADS

SCHEMATIC

LEADS

S#22/8"	COMMON	WHITE	
S#22/8"	120V input	BLACK	
S#22/8"	230V/250VA	BROWN	

LEADS: S=Multistranded wire. Length tolerance: +/- 1/2".  
Manufacturing tolerance is +/- 3%.

NOMINAL SUPPLY: 120V +/-10%  
RATED PRIMARY CURRENT: 2.2A  
RATED FREQUENCY: 60 Hz  
TEMP. RISE AT RATED LOAD: 45 °C

DIMENSIONS/WEIGHT:

OD = 3.9"  
H = 1.7"  
WEIGHT = 2.6 LBS.

MOUNTING:

WASHER/PADS = 70mm  
THICKNESS = 0.05"  
HOLE DIAMETER = 0.25"

CORE DATA:

CORE # 900115  
CORE LOSS = 0.7 W  
NO-LOAD CURRENT = 15 mA

Dimensions stated above are nominal. Tolerance is 10%.

OTHER SPECIFICATIONS: Transformer is UL recognized to UL 1411 and CUL certified to CSA C22.2 No. 1-M90 standards.

Label:

SPEC DATE: 06/17/05

By:

(Logo)

Auto-Transformer # AZ85615  
Input: 120Vac 60Hz blk-wht  
Output: 230V 250VA brn-wht  
(date code)