

DATA SHEET FOR

TRANSFORMER # 713.1202

Made for STANDARD

page 1 of 1

<u>LEADS</u>	<u>SCHEMATIC</u>				<u>LEADS</u>
M#24/8" 0V WHITE	┌───┐		┌───┐	BROWN 0V	S#22/8"
				UO =132.6V RMS	
M#24/8" 117V YELLOW	┌───┐		┌───┐	RED 117V RMS / 0.60A RMS	S#22/8"
M#24/8" 0V ORANGE	┌───┐		┌───┐	ORANGE 0V	S#22/8"
				UO =132.6V RMS	
M#24/8" 117V BLACK	┌───┐		┌───┐	YELLOW 117V RMS / 0.60A RMS	S#22/8"

PRIMARIES ARE INSIDE A SLEEVE.

Primaries must be connected together in series or in parallel.

LEADS: S=Multistranded Lead wire. M=Magnet wire self-leads. Length tolerance: +/-1/2".
 Manufacturing tolerance is +/- 3%.

NOMINAL SUPPLY: 117/234V +/-10%
 RATED PRIMARY CURRENT: 1.4/0.7A

RATED FREQ.: 50/60 Hz
 TEMP RISE AT RATED LOAD = 70 C

DIMENSIONS/WEIGHT:

OD = 3.9"
 H = 1.9"
 WEIGHT = 3.0 LBS.

MOUNTING:

WASHER/PADS = 70 mm
 THICKNESS = 0.05"
 HOLE DIAMETER = 0.25"

CORE DATA:

CORE # 900140
 NO-LOAD LOSS = 0.9 W
 NO-LOAD AMPS = 7.9 mA

Dimensions stated above are nominal. Tolerance is 10%

SPECIFICATIONS: Transformer is UL recognized to UL 1411 and CSA certified to CSA C22.2 No. 66. OTHER

SPEC DATE: 10/16/96	┌───┐	Label:	┌───┐
		Transformer # 713.1202 (201402)	
		Prim. 2x117V 50/60Hz bk(wh-ye/or-bk)	
		Sec. 2x117V/ 0.60A br-re/or-ye	
BY: _____	(LOGO)	(date code)	┌───┐
	┌───┐		┌───┐