









DATA SHEET FOR TRANSFORMER # 732.1202

Made for STANDARD

<u>LEADS</u>		<u>SCHEMATIC</u>				<u>LEADS</u>
M#20/8"	0V	white			brown 0V	M#21/8"
M#20/8"	117V	yellow			red 117V rms at 1.37A rms	M#21/8"
M#20/8"	0V	orange			orange 0V	M#21/8"
M#20/8"	117V	black			yellow 117V rms at 1.37A rms	M#21/8"

PRIMARY LEADS ARE INSIDE A BLACK SLEEVE. Primaries must be connected in series or in parallel.
 LEADS: S=Multistranded lead wire. M=Magnet wire self-leads. Length tolerance: +/- 1/2".
 Manufacturing tolerance is 3%.

NOMINAL SUPPLY: 117/234 V +/- 10% **RATED FREQ.:** 50/60 Hz
RATED PRIMARY CURRENT: 3.0/1.5 A **TEMP RISE AT RATED LOAD =** 58 C

<u>DIMENSIONS/WEIGHT:</u>	<u>MOUNTING:</u>	<u>CORE DATA:</u>
OD = 4.9"	WASHER/PADS = 90 mm	CORE # 900328
H = 2.2"	THICKNESS = .06"	NO-LOAD LOSS = 1.5 W
WEIGHT = 5.9 lbs.	HOLE DIAMETER = .25"	NO-LOAD AMPS = 15 mA

Dimensions stated above are nominal. Tolerance is 10%.

OTHER SPECIFICATIONS: Transformer is UL recognized to UL 1411 and CSA certified to CSA C22.2 No. 66-1988.

SPEC. DATE: 03-12-92 BY: _____	Label: (LOGO)	Transformer # 732.1202 Prim. 2x117V 50Hz bk(wh-ye/or-bk) Sec. 2x117V / 1.37A br-re/or-ye (date code)
---------------------------------------	----------------------	---