









DATA SHEET FOR TRANSFORMER # 738.1202

Made for STANDARD

<u>LEADS</u>		<u>SCHEMATIC</u>				<u>LEADS</u>	
M#19/8"	0V	white			brown	0V	M#20/8"
M#19/8"	117V	yellow			red	117V rms at 1.65A rms	M#20/8"
M#19/8"	0V	orange			orange	0V	M#20/8"
M#19/8"	117V	black			yellow	117V rms at 1.65A rms	M#20/8"

PRIMARY LEADS ARE INSIDE A BLACK SLEEVE. Primaries must be connected in series or in parallel.
LEADS: S=Multistranded lead wire. M=Magnet wire self-leads. Length tolerance: +/- 1/2".
Manufacturing tolerance is 3%.

NOMINAL SUPPLY: 117/234 V +/- 10% RATED FREQ.: 50/60 Hz
RATED PRIMARY CURRENT: 3.6/1.8 A TEMP RISE AT RATED LOAD = 59 C

<u>DIMENSIONS/WEIGHT:</u>	<u>MOUNTING:</u>	<u>CORE DATA:</u>
OD = 4.9"	WASHER/PADS = 90 mm	CORE # 900360
H = 2.4"	THICKNESS = .06"	NO-LOAD LOSS = 1.7 W
WEIGHT = 6.7 lbs.	HOLE DIAMETER = .25"	NO-LOAD AMPS = 17 mA

Dimensions stated above are nominal. Tolerance is 10%.

OTHER SPECIFICATIONS: Transformer is UL recognized to UL 1411 and CSA certified to CSA C22.2 No. 66-1988.

SPEC. DATE: 03-12-92 BY: _____	Label: (LOGO)	Transformer # 738.1202 Prim. 2x117V 50Hz bk(wh-ye/or-bk) Sec. 2x117V / 1.65A br-re/or-ye (date code)
---------------------------------------	----------------------	---