

DATA SHEET FOR TRANSFORMER # 798.1202

Made for STANDARD

<u>LEADS</u>	<u>SCHEMATIC</u>		<u>LEADS</u>
M#15/8" 0V white	□	□	M#16/8" brown 0V
M#15/8" 117V yellow	□	□	M#16/8" red 117V rms at 4.27A rms
M#15/8" 0V orange	□	□	M#16/8" orange 0V
M#15/8" 117V black	□	□	M#16/8" yellow 117V rms at 4.27A rms

(U0=121.9V rms)

(U0=121.9V rms)

PRIMARY LEADS ARE INSIDE A BLACK SLEEVE. Primaries must be connected in series or in parallel.
 LEADS: S=Multistranded lead wire. M=Magnet wire self-leads. Length tolerance: +/- 1/2".
 Manufacturing tolerance is 3%.

NOMINAL SUPPLY: 117/234 V +/- 10% **RATED FREQ.:** 50/60 Hz
RATED PRIMARY CURRENT: 9.0/4.5 A **TEMP RISE AT RATED LOAD =** 58 C

<u>DIMENSIONS/WEIGHT:</u> OD = 6.4" H = 3.3" WEIGHT =17.0 lbs.	<u>MOUNTING:</u> WASHER/PADS = 145 mm THICKNESS = .08" HOLE DIAMETER = .32"	<u>CORE DATA:</u> CORE # 1200 NO-LOAD LOSS =5.3 W NO-LOAD AMPS = 49 mA
--	---	--

Dimensions stated above are nominal. Tolerance is 10%.

OTHER SPECIFICATIONS: Transformer is UL recognized to UL 1411 and CSA certified to CSA C22.2 No. 66-1988.

SPEC.DATE: 03-12-92 BY: _____	Label: (LOGO)	Transformer # 798.1202 Prim. 2x117V 50Hz bk(wh-ye/or-bk) Sec. 2x117V / 4.27A br-re/or-y (date code)
--------------------------------------	----------------------	--