

DATA SHEET FOR  
TRANSFORMER # 901.1201

Made for STANDARD

page 1 of 1

<u>LEADS</u>	<u>SCHEMATIC</u>	<u>LEADS</u>	
S#22/12"      0V            WHITE		S#22/12"	
S#22/12"      100V           BLUE		WHITE      0V A/R THERMAL FUSE 120° C	S#22/12"
S#22/12"      120V           YELLOW		BLACK      UO = 138.7V RMS 120V RMS / 100VA	S#22/12"
S#22/12"      0V              ORANGE		VIOLET      STATIC SHIELD	S#22/12"
S#22/12"      100V           RED			
S#22/12"      120V           BLACK			

PRIMARIES ARE INSIDE A SLEEVE.  
Primaries must be connected together in series or in parallel.  
 LEADS: S=Multistranded wire. M=Magnet wire self-leads. Length tolerance: +/- 1/2".  
 Manufacturing tolerance is +/- 3%.

NOMINAL SUPPLY:            100/120/220/240V +/-10%  
 RATED PRIMARY CURRENT: 1.2/1.0/0.5/0.5A  
 RATED FREQUENCY:        50/60Hz  
 TEMP. RISE AT RATED LOAD: 60° C

DIMENSIONS/WEIGHT:  
 OD = 3.9"  
 H = 1.8"  
 WEIGHT = 2.5 LBS.

MOUNTING:  
 WASHER/PADS = 70 mm.  
 THICKNESS = 0.05"  
 HOLE DIAMETER = 0.25"

CORE DATA:  
 CORE # 900115  
 CORE LOSS = 0.7 W  
 NO-LOAD CURRENT = 6.4 mA

Dimensions stated above are nominal. Tolerance is 10%.

OTHER SPECIFICATIONS: Transformer is UL recognized to UL 544 and UL 2601-1. UL certified to CSA C22.2 No. 601-1 and TUV certified to EN60601 and EN60742. CE compliance. Class B insulation. Leakage current < 50µA.

	Label:	
SPEC DATE: 06/15/05	(Logo)	Transformer # ZMO46190 (901.1201)        (301001) REF. B4316190 (date code)
By:		

