

DATA SHEET FOR TRANSFORMER # 901.1202

Made for STANDARD

<u>LEADS</u>	<u>SCHEMATIC</u>	<u>LEADS</u>
S#22/12" 0V	WHITE	BROWN 0V
S#22/12" 100V	BLUE	A/R THERMAL FUSE 120°C UO = 136.3V RMS
S#22/12" 120V	YELLOW	RED 120V RMS / 50VA
S#22/12" 0V	ORANGE	ORANGE 0V
S#22/12" 100V	RED	A/R THERMAL FUSE 120°C UO = 136.3V RMS
S#22/12" 120V	BLACK	YELLOW 120V RMS / 50VA
		VIOLET STATIC SHIELD

PRIMARIES ARE INSIDE A SLEEVE.
Primaries must be connected together in series or in parallel.
 LEADS: S=Multistranded Lead wire. Length tolerance: +/- 1/2".
 Manufacturing tolerance is +/- 3%.

NOMINAL SUPPLY: 100/120/220/240V +/-10%
 RATED PRIMARY CURRENT: 1.2/1.0/0.6/0.6/0.5A
 RATED FREQUENCY: 50/60 Hz
 TEMP. RISE AT RATED LOAD: 54°C

<u>DIMENSIONS/WEIGHT:</u>	<u>MOUNTING:</u>	<u>CORE DATA:</u>
OD = 4.0"	WASHER/PADS = 70 M.M.	CORE # 900115
H = 1.8"	THICKNESS = 0.05"	NO-LOAD LOSS = 0.7 W
WEIGHT = 2.4 LBS.	HOLE DIAMETER = 0.25"	NO-LOAD AMPS = 7 mA

Dimensions stated above are nominal. Tolerance is 10%.

OTHER SPECIFICATIONS: Transformer is UL recognized to UL544 and UL 2601-1. CSA certified to CSA C22.2 No. 66 and TUV certified to EN60601 and EN60742. CE compliance. Class B insulation. Leakage current < 50µA.

SPEC DATE: 06/15/05	Label:	Transformer # ZM845238 (901.1202)
		(301002)
By:	(Logo)	REF. B4315238
		(date code)