

DATA SHEET FOR  
TRANSFORMER # 902.1201

Made for STANDARD

page 1 of 1

<u>LEADS</u>	<u>SCHEMATIC</u>	<u>LEADS</u>	
S#22/12"      0V            WHITE		S#22/12"	
S#22/12"      100V           BLUE		WHITE      0V A/R THERMAL FUSE 120° C	S#22/12"
S#22/12"      120V           YELLOW		UO = 133.4V RMS 120V RMS / 200VA	S#22/12"
S#22/12"      0V              ORANGE		VIOLET            STATIC SHIELD	S#22/12"
S#22/12"      100V           RED			
S#22/12"      120V           BLACK			

PRIMARIES ARE INSIDE A SLEEVE.

Primaries must be connected together in series or in parallel.

LEADS: S=Multistranded wire. M=Magnet wire self-leads. Length tolerance: +/- 1/2".  
Manufacturing tolerance is +/- 3%.

NOMINAL SUPPLY:            100/120/220/240V +/-10%  
RATED PRIMARY CURRENT: 2.2/1.9/1.0/0.9A  
RATED FREQUENCY:        50/60Hz  
TEMP. RISE AT RATED LOAD: 63° C

DIMENSIONS/WEIGHT:  
OD = 4.5"  
H = 2.1"  
WEIGHT = 4.3 LBS.

MOUNTING:  
WASHER/PADS = 90 mm.  
THICKNESS = 0.06"  
HOLE DIAMETER = 0.25"

CORE DATA:  
CORE # 900225  
CORE LOSS = 1.2 W  
NO-LOAD CURRENT = 10.5 mA

Dimensions stated above are nominal. Tolerance is 10%.

OTHER SPECIFICATIONS: Transformer is UL recognized to UL 544 and UL 2601-1. UL certified to CSA C22.2 No. 601-1 and TUV certified to EN60601 and EN60742. CE compliance. Class B insulation. Leakage current < 50µA.

Label:

SPEC DATE: 06/15/05

(Logo)

By:

Transformer # ZMO46191  
(902.1201)            (302001)  
REF. B4316191  
(date code)

