


DATA SHEET FOR
TRANSFORMER # 902.1202

Made for STANDARD

<u>LEADS</u>		<u>SCHEMATIC</u>				<u>LEADS</u>	
S#22/12"	0V	WHITE		BROWN	0V	S#22/12"	
S#22/12"	100V	BLUE		A/R THERMAL FUSE 120°C			
S#22/12"	120V	YELLOW		RED	120V RMS / 100VA		S#22/12"
S#22/12"	0V	ORANGE		ORANGE	0V		S#22/12"
S#22/12"	100V	RED		A/R THERMAL FUSE 120°C	UO = 132.2V RMS		S#22/12"
S#22/12"	120V	BLACK		YELLOW	120V RMS / 100VA		S#22/12"
				VIOLET	STATIC SHIELD	S#22/12"	

PRIMARIES ARE INSIDE A SLEEVE.

Primaries must be connected together in series or in parallel.

LEADS: S=Multistranded Lead wire. Length tolerance: +/- 1/2".

Manufacturing tolerance is +/- 3%.

NOMINAL SUPPLY: 100/120/220/240V +/-10%
 RATED PRIMARY CURRENT: 2.3/1.9/1.2/1.1/1.0A
 RATED FREQUENCY: 50/60 Hz
 TEMP. RISE AT RATED LOAD: 59°C

DIMENSIONS/WEIGHT:

OD = 4.6"
 H = 2.2"
 WEIGHT = 4.2 LBS.

MOUNTING:

WASHER/PADS = 90 M.M./3.5"
 THICKNESS = .06"
 HOLE DIAMETER = .25"

CORE DATA:

CORE # 900225
 NO-LOAD LOSS = 1.2 W
 NO-LOAD AMPS = 11 mA

Dimensions stated above are nominal. Tolerance is 10%.

OTHER SPECIFICATIONS: Transformer is UL recognized to UL544 and UL 2601-1. CSA certified to CSA C22.2 No. 66 and TUV certified to EN60601 and EN60742. CE compliance. Class B insulation. Leakage current < 50µA.

Label:

Transformer # ZM845237 (902.1202)
 (302002)

SPEC DATE: 06/15/05

(Logo)

REF. B4315237

By:

(date code)