


DATA SHEET FOR  
TRANSFORMER # 903.1202

Made for STANDARD

<u>LEADS</u>		<u>SCHEMATIC</u>				<u>LEADS</u>	
S#22/12"	0V	WHITE		BROWN	0V	S#22/12"	
S#22/12"	100V	BLUE		A/R THERMAL FUSE 120°C			
S#22/12"	120V	YELLOW		RED	120V RMS / 150VA		S#22/12"
S#22/12"	0V	ORANGE		ORANGE	0V		S#22/12"
S#22/12"	100V	RED		A/R THERMAL FUSE 120°C	UO = 130.5V RMS		
S#22/12"	120V	BLACK		YELLOW	120V RMS / 150VA		S#22/12"
				VIOLET	STATIC SHIELD	S#22/12"	

PRIMARIES ARE INSIDE A SLEEVE.  
Primaries must be connected together in series or in parallel.  
 LEADS: S=Multistranded Lead wire. Length tolerance: +/- 1/2".  
 Manufacturing tolerance is +/- 3%.

NOMINAL SUPPLY: 100/120/220/240V +/-10%  
 RATED PRIMARY CURRENT: 3.3/2.8/1.5/1.4A  
 RATED FREQUENCY: 50/60 Hz  
 TEMP. RISE AT RATED LOAD: 57°C

<u>DIMENSIONS/WEIGHT:</u>	<u>MOUNTING:</u>	<u>CORE DATA:</u>
OD = 5.6"	WASHER/PADS = 110 M.M.	CORE # 900370
H = 2.3"	THICKNESS = 0.08"	NO-LOAD LOSS = 1.7 W
WEIGHT = 6.0 LBS.	HOLE DIAMETER = 0.32"	NO-LOAD AMPS = 16 mA

Dimensions stated above are nominal. Tolerance is 10%.

OTHER SPECIFICATIONS: Transformer is UL recognized to UL544 and UL 2601-1. CSA certified to CSA C22.2 No. 66 and TUV certified to EN60601 and EN60742. CE compliance. Class B insulation. Leakage current < 50µA.

Label: Transformer # ZM845236 (903.1202)  
 (315002)  
 REF. B4315236  
 (date code)

SPEC DATE: 06/15/05

By: (Logo)