

DATA SHEET FOR  
TRANSFORMER # 904.1201

Made for STANDARD

page 1 of 1

<u>LEADS</u>	<u>SCHEMATIC</u>	<u>LEADS</u>
S#20/12"      0V            WHITE S#20/12"      100V           BLUE S#20/12"      120V           YELLOW S#20/12"      0V              ORANGE S#20/12"      100V           RED S#20/12"      120V           BLACK		WHITE      0V A/R THERMAL FUSE 120° C UO = 128.7V RMS 120V RMS / 400VA BLACK VIOLET      STATIC SHIELD S#18/12" S#18/12" S#22/12"

PRIMARIES ARE INSIDE A SLEEVE.

Primaries must be connected together in series or in parallel.

LEADS: S=Multistranded wire. M=Magnet wire self-leads. Length tolerance: +/- 1/2".  
Manufacturing tolerance is +/- 3%.

NOMINAL SUPPLY:            100/120/220/240V +/-10%  
 RATED PRIMARY CURRENT: 4.3/3.6/2.0/1.8A  
 RATED FREQUENCY:        50/60Hz  
 TEMP. RISE AT RATED LOAD: 62° C

DIMENSIONS/WEIGHT:  
 OD = 5.5"  
 H = 2.3"  
 WEIGHT = 7.3 LBS.

MOUNTING:  
 WASHER/PADS = 110 mm.  
 THICKNESS = 0.08"  
 HOLE DIAMETER = 0.32"

CORE DATA:  
 CORE # 900371  
 CORE LOSS = 2.0 W  
 NO-LOAD CURRENT = 18.1 mA

Dimensions stated above are nominal. Tolerance is 10%.

OTHER SPECIFICATIONS: Transformer is UL recognized to UL 544 and UL 2601-1. UL certified to CSA C22.2 No. 601-1 and TUV certified to EN60601 and EN60742. CE compliance. Class B insulation. Leakage current < 50µA.

Label:

SPEC DATE: 06/15/05

By:

(Logo)

Transformer # ZMO46193  
 (904.1201)      (304001)  
 REF. B4316193  
 (date code)

