

DATA SHEET FOR
TRANSFORMER # 906.1201

Made for STANDARD

<u>LEADS</u>	<u>SCHEMATIC</u>	<u>LEADS</u>	
S#18/12" 0V WHITE		S#18/12"	
S#18/12" 100V BLUE		WHITE 0V A/R THERMAL FUSE 120° C	S#18/12"
S#18/12" 120V YELLOW		BLACK UO = 127.9V RMS 120V RMS / 600VA	S#18/12"
S#18/12" 0V ORANGE		VIOLET STATIC SHIELD	S#20/12"
S#18/12" 100V RED			
S#18/12" 120V BLACK			

PRIMARIES ARE INSIDE A SLEEVE.
Primaries must be connected together in series or in parallel.
LEADS: S=Multistranded wire. M=Magnet wire self-leads. Length tolerance: +/- 1/2".
 Manufacturing tolerance is +/- 3%.

NOMINAL SUPPLY: 100/120/220/240V +/-10%
 RATED PRIMARY CURRENT: 6.4/5.4/2.9/2.7A
 RATED FREQUENCY: 50/60Hz
 TEMP. RISE AT RATED LOAD: 64° C

<u>DIMENSIONS/WEIGHT:</u>	<u>MOUNTING:</u>	<u>CORE DATA:</u>
OD = 6.5"	WASHER/PADS = 145 mm.	CORE # 900639
H = 2.5"	THICKNESS = 0.08"	CORE LOSS = 3.1 W
WEIGHT = 10.4 LBS.	HOLE DIAMETER = 0.40"	NO-LOAD CURRENT = 27.9 mA

Dimensions stated above are nominal. Tolerance is 10%.

OTHER SPECIFICATIONS: Transformer is UL recognized to UL 544 and UL 2601-1. UL certified to CSA C22.2 No. 601-1 and TUV certified to EN60601 and EN60742. CE compliance. Class B insulation. Leakage current < 50µA.

	Label:	
SPEC DATE: 06/15/05	(Logo)	Transformer # ZMO46194 (906.1201) (306001) REF. B04316194 (date code)
By:		

