


DATA SHEET FOR
TRANSFORMER # 906.1202

Made for STANDARD

<u>LEADS</u>		<u>SCHEMATIC</u>				<u>LEADS</u>	
S#18/12"	0V	WHITE		BROWN	0V	S#20/12"	
S#18/12"	100V	BLUE			A/R THERMAL FUSE 120°C		
S#18/12"	120V	YELLOW			RED	UO = 128.0V RMS	S#20/12"
S#18/12"	0V	ORANGE			ORANGE	120V RMS / 300VA	
S#18/12"	100V	RED			A/R THERMAL FUSE 120°C	UO = 128.0V RMS	S#20/12"
S#18/12"	120V	BLACK			YELLOW	120V RMS / 300VA	S#20/12"
				VIOLET	STATIC SHIELD	S#18/12"	

PRIMARIES ARE INSIDE A SLEEVE.

Primaries must be connected together in series or in parallel.

LEADS: S=Multistranded Lead wire. Length tolerance: +/- 1/2".

Manufacturing tolerance is +/- 3%.

NOMINAL SUPPLY: 100/120/220/240V +/-10%
 RATED PRIMARY CURRENT: 6.5/5.4/3.3/3.0/2.7A
 RATED FREQUENCY: 50/60 Hz
 TEMP. RISE AT RATED LOAD: 62°C

DIMENSIONS/WEIGHT:

OD = 6.5"
 H = 2.6"
 WEIGHT = 10.5 LBS.

MOUNTING:

WASHER/PADS = 145 M.M./5.7"
 THICKNESS = .08"
 HOLE DIAMETER = .40"

CORE DATA:

CORE # 900622
 NO-LOAD LOSS = 3.1 W
 NO-LOAD AMPS = 28 mA

Dimensions stated above are nominal. Tolerance is 10%.

OTHER SPECIFICATIONS: Transformer is UL recognized to UL544 and UL 2601-1. CSA certified to CSA C22.2 No. 66 and TUV certified to EN60601 and EN60742. CE compliance. Class B insulation. Leakage current < 50µA.

Label:

Transformer # ZM845234
 (306002) (906.1202)

SPEC DATE: 06/15/05

(Logo)

REF. B04315234

By:

(date code)