

DATA SHEET FOR  
TRANSFORMER # 908.1201

Made for STANDARD

<u>LEADS</u>			<u>SCHEMATIC</u>	<u>LEADS</u>		
S#18/12"	0V	WHITE		WHITE	0V	S#16/12"
S#18/12"	100V	BLUE		BLACK	A/R THERMAL FUSE 120° C UO = 126.5V RMS	S#16/12"
S#18/12"	120V	YELLOW		VIOLET	120V RMS / 760VA	S#20/12"
S#18/12"	0V	ORANGE			STATIC SHIELD	
S#18/12"	100V	RED				
S#18/12"	120V	BLACK				

PRIMARIES ARE INSIDE A SLEEVE.

Primaries must be connected together in series or in parallel.

LEADS: S=Multistranded wire. M=Magnet wire self-leads. Length tolerance: +/- 1/2".  
Manufacturing tolerance is +/- 3%.

NOMINAL SUPPLY: 100/120/220/240V +/-10%  
RATED PRIMARY CURRENT: 8.0/6.7/3.7/3.3A  
RATED FREQUENCY: 50/60Hz  
TEMP. RISE AT RATED LOAD: 64° C

DIMENSIONS/WEIGHT:  
OD = 6.5"  
H = 2.8"  
WEIGHT = 13.0 LBS.

MOUNTING:  
WASHER/PADS = 145 mm.  
THICKNESS = 0.08"  
HOLE DIAMETER = 0.40"

CORE DATA:  
CORE # 800  
CORE LOSS = 3.5 W  
NO-LOAD CURRENT = 31.9 mA

Dimensions stated above are nominal. Tolerance is 10%.

OTHER SPECIFICATIONS: Transformer is UL recognized to UL 544 and UL 2601-1. UL certified to CSA C22.2 No. 601-1 and TUV certified to EN60601 and EN60742. CE compliance. Class B insulation. Leakage current < 50µA.

Label:

SPEC DATE: 06/15/05

(Logo)

By:

Transformer # ZMO46195  
(908.1201) (307601)  
REF. B4316195  
(date code)