

DATA SHEET FOR
TRANSFORMER # 908.1202

Made for STANDARD

<u>LEADS</u>		<u>SCHEMATIC</u>				<u>LEADS</u>	
S#16/12"	0V	WHITE		BROWN	0V	S#18/12"	
S#16/12"	100V	BLUE		A/R THERMAL FUSE 120°C			
S#16/12"	120V	YELLOW		RED	120V RMS / 380VA		S#18/12"
S#16/12"	0V	ORANGE		ORANGE	0V		S#18/12"
S#16/12"	100V	RED		A/R THERMAL FUSE 120°C			
S#16/12"	120V	BLACK		YELLOW	120V RMS / 380VA		S#18/12"
				VIOLET	STATIC SHIELD	S#18/12"	

PRIMARIES ARE INSIDE A SLEEVE.
Primaries must be connected together in series or in parallel.
 LEADS: S=Multistranded Lead wire. Length tolerance: +/- 1/2".
 Manufacturing tolerance is +/- 3%.

NOMINAL SUPPLY: 100/120/220/240V +/-10%
 RATED PRIMARY CURRENT: 8.1/6.7/4.1/3.7/3.4A
 RATED FREQUENCY: 50/60 Hz
 TEMP. RISE AT RATED LOAD: 63°C

<u>DIMENSIONS/WEIGHT:</u>	<u>MOUNTING:</u>	<u>CORE DATA:</u>
OD = 6.5"	WASHER/PADS = 145 M.M./5.7"	CORE # 800
H = 2.8"	THICKNESS = .08"	NO-LOAD LOSS = 3.5 W
WEIGHT = 12.5 LBS.	HOLE DIAMETER = .40"	NO-LOAD AMPS = 31 mA

Dimensions stated above are nominal. Tolerance is 10%.

OTHER SPECIFICATIONS: Transformer is UL recognized to UL544 and UL 2601-1. CSA certified to CSA C22.2 No. 66 and TUV certified to EN60601 and EN60742. CE compliance. Class B insulation. Leakage current < 50µA.

Label: Transformer # ZM845233
 (307602) (908.1202)
 REF. B4315233
 (date code)

SPEC DATE: 06/15/05

By: (Logo)