

DATA SHEET FOR
TRANSFORMER # 910.1201

Made for STANDARD

page 1 of 1

<u>LEADS</u>	<u>SCHEMATIC</u>	<u>LEADS</u>	
S#16/12" 0V WHITE		S#14/12"	
S#16/12" 100V BLUE		WHITE 0V A/R THERMAL FUSE 120° C	S#14/12"
S#16/12" 120V YELLOW		BLACK UO = 124.5V RMS 120V RMS / 1000VA	S#14/12"
S#16/12" 0V ORANGE		VIOLET STATIC SHIELD	S#18/12"
S#16/12" 100V RED			
S#16/12" 120V BLACK			

PRIMARIES ARE INSIDE A SLEEVE.
Primaries must be connected together in series or in parallel.
LEADS: S=Multistranded wire. M=Magnet wire self-leads. Length tolerance: +/- 1/2".
 Manufacturing tolerance is +/- 3%.

NOMINAL SUPPLY: 100/120/220/240V +/-10%
 RATED PRIMARY CURRENT: 10.5/8.7/4.8/4.4A
 RATED FREQUENCY: 50/60Hz
 TEMP. RISE AT RATED LOAD: 58° C

DIMENSIONS/WEIGHT:
 OD = 6.5"
 H = 3.6"
 WEIGHT = 17.2 LBS.

MOUNTING:
 SPECIFIED BY CUSTOMER

CORE DATA:
 CORE # 1200
 CORE LOSS = 5.3 W
 NO-LOAD CURRENT = 47.9 mA

Dimensions stated above are nominal. Tolerance is 10%.

OTHER SPECIFICATIONS: Transformer is UL recognized to UL 544 and UL 2601-1. UL certified to CSA C22.2 No. 601-1 and TUV certified to EN60601 and EN60742. CE compliance. Class B insulation. Leakage current < 50µA.

	Label:	
SPEC DATE: 06/15/05	(Logo)	Transformer # ZMO46196 (910.1201) (310001) REF. B4316196 (date code)
By:		

