

DATA SHEET FOR
TRANSFORMER # 910.1202

Made for STANDARD

<u>LEADS</u>		<u>SCHEMATIC</u>				<u>LEADS</u>	
S#16/12"	0V	WHITE		BROWN	0V	S#16/12"	
S#16/12"	100V	BLUE		A/R THERMAL FUSE 120°C	UO = 124.7V RMS		
S#16/12"	120V	YELLOW		RED	120V RMS / 500VA		S#16/12"
S#16/12"	0V	ORANGE		ORANGE	0V		S#16/12"
S#16/12"	100V	RED		A/R THERMAL FUSE 120°C	UO = 124.7V RMS		S#16/12"
S#16/12"	120V	BLACK		YELLOW	120V RMS / 500VA		S#16/12"
			VIOLET	STATIC SHIELD		S#18/12"	

PRIMARIES ARE INSIDE A SLEEVE.
Primaries must be connected together in series or in parallel.
 LEADS: S=Multistranded Lead wire. Length tolerance: +/- 1/2".
 Manufacturing tolerance is +/- 3%.

NOMINAL SUPPLY: 100/120/220/240V +/-10%
 RATED PRIMARY CURRENT: 11/9/6/5/5A
 RATED FREQUENCY: 50/60 Hz
 TEMP. RISE AT RATED LOAD: 60°C

DIMENSIONS/WEIGHT:
 OD = 7.0"
 H = 3.7"
 WEIGHT = 17.5 LBS.

MOUNTING:
 SPECIFIED BY CUSTOMER

CORE DATA:
 CORE # 1200
 NO-LOAD LOSS = 5.3 W
 NO-LOAD AMPS = 48 mA

Dimensions stated above are nominal. Tolerance is 10%.

OTHER SPECIFICATIONS: Transformer is UL recognized to UL544 and UL 2601-1. CUL certified to CSA C22.2 No. 601-1 and TUV certified to EN60601-1 and EN60742. CE compliance. Class B insulation. Leakage current < 50µA.

Label: Transformer # ZM845049
 (310002) (910.1202)
 REF. B04315049
 (date code)

SPEC DATE: 06/15/05

By: (Logo)