



DATA SHEET FOR
TRANSFORMER # 915.1201

Made for STANDARD

<u>LEADS</u>		<u>SCHEMATIC</u>		<u>LEADS</u>		
S#14/12"	0V	WHITE		WHITE	0V	S#12/12"
S#14/12"	100V	BLUE		A/R THERMAL FUSE 120° C	UO = 124.5V RMS	S#12/12"
S#14/12"	120V	YELLOW		BLACK	120V RMS / 1500VA	S#12/12"
S#14/12"	0V	ORANGE		VIOLET	STATIC SHIELD	S#18/12"
S#14/12"	100V	RED				
S#14/12"	120V	BLACK				

PRIMARIES ARE INSIDE A SLEEVE.

Primaries must be connected together in series or in parallel.

LEADS: S=Multistranded wire. M=Magnet wire self-leads. Length tolerance: +/- 1/2".

Manufacturing tolerance is +/- 3%.

NOMINAL SUPPLY: 100/120/220/240V +/-10%
 RATED PRIMARY CURRENT: 15.7/13.0/7.1/6.5A
 RATED FREQUENCY: 50/60Hz
 TEMP. RISE AT RATED LOAD: 60° C


DIMENSIONS/WEIGHT:
 OD = 8.2"
 H = 3.6"
 WEIGHT = 23.6 LBS.

MOUNTING:
 SPECIFIED BY CUSTOMER

CORE DATA:
 CORE # 1700
 CORE LOSS = 6.7 W
 NO-LOAD CURRENT = 59.1 mA

Dimensions stated above are nominal. Tolerance is 10%.

OTHER SPECIFICATIONS: Transformer is UL recognized to UL 544 and UL 2601-1. UL certified to CSA C22.2 No. 601-1 and TUV certified to EN60601 and EN60742. CE compliance. Class B insulation. Leakage current < 50µA.

Label: 
 Transformer # ZMO46197
 (915.1201) (315001)
 REF. B4316197
 (date code)

SPEC DATE: 06/15/05

By: (Logo)

TOROID CORPORATION of MD