

DATA SHEET FOR
TRANSFORMER # 920.1201

Made for STANDARD

<u>LEADS</u>	<u>SCHEMATIC</u>	<u>LEADS</u>
S#12/12" 0V WHITE S#12/12" 100V BLUE S#12/12" 120V YELLOW S#12/12" 0V ORANGE S#12/12" 100V RED S#12/12" 120V BLACK		WHITE 0V A/R THERMAL FUSE 120° C UO = 124.1V RMS BLACK 120V RMS / 2000VA VIOLET STATIC SHIELD S#10/12" S#10/12" S#18/12"

PRIMARIES ARE INSIDE A SLEEVE.
Primaries must be connected together in series or in parallel.
 LEADS: S=Multistranded wire. M=Magnet wire self-leads. Length tolerance: +/- 1/2".
 Manufacturing tolerance is +/- 3%.

NOMINAL SUPPLY: 100/120/220/240V +/-10%
 RATED PRIMARY CURRENT: 20.8/17.3/9.5/8.7A
 RATED FREQUENCY: 50/60Hz
 TEMP. RISE AT RATED LOAD: 58° C

DIMENSIONS/WEIGHT:
 OD = 9.2"
 H = 4.1"
 WEIGHT = 31.0 LBS.

MOUNTING:
 SPECIFIED BY CUSTOMER

CORE DATA:
 CORE # 902047
 CORE LOSS = 8.4 W
 NO-LOAD CURRENT = 71.7 mA

Dimensions stated above are nominal. Tolerance is 10%.

OTHER SPECIFICATIONS: Transformer is UL recognized to UL 544 and UL 2601-1. UL certified to CSA C22.2 No. 601-1 and TUV certified to EN60601 and EN60742. CE compliance. Class B insulation. Leakage current < 50µA.

	Label:	
SPEC DATE: 06/15/05 By:	(Logo)	Transformer # ZMO46198 (920.1201) (320001) REF. B4316198 (date code)

