

DATA SHEET FOR
TRANSFORMER # 925.1201

Made for STANDARD

page 1 of 1

<u>LEADS</u>			<u>SCHEMATIC</u>	<u>LEADS</u>		
S#12/12"	0V	WHITE		WHITE	0V	S#10/12"
S#12/12"	100V	BLUE		BLACK	A/R THERMAL FUSE 120° C UO = 123.1V RMS 120V RMS / 2500VA	S#10/12"
S#12/12"	120V	YELLOW		GRAY	A/R THERMAL FUSE 120° C/6A	S#18/12"
S#12/12"	0V	ORANGE		GRAY		S#18/12"
S#12/12"	100V	RED		VIOLET	STATIC SHIELD	S#18/12"
S#12/12"	120V	BLACK				

PRIMARIES ARE INSIDE A SLEEVE.

Primaries must be connected together in series or in parallel.

LEADS: S=Multistranded wire. M=Magnet wire self-leads. Length tolerance: +/- 1/2".
Manufacturing tolerance is +/- 3%.

NOMINAL SUPPLY: 100/120/220/240V +/-10%
RATED PRIMARY CURRENT: 25.9/21.6/11.8/10.8A
RATED FREQUENCY: 50/60Hz
TEMP. RISE AT RATED LOAD: 61° C

DIMENSIONS/WEIGHT:
OD = 10.0"
H = 4.1"
WEIGHT = 38.0 LBS.

MOUNTING:
SPECIFIED BY CUSTOMER

CORE DATA:
CORE # 902428
CORE LOSS = 10.2 W
NO-LOAD CURRENT = 86.5 mA

Dimensions stated above are nominal. Tolerance is 10%.

OTHER SPECIFICATIONS: Transformer is UL recognized to UL 544 and UL 2601-1. UL certified to CSA C22.2 No. 601-1 and TUV certified to EN60601 and EN60742. CE compliance. Class B insulation. Leakage current < 50µA.

Label:

SPEC DATE: 06/15/05

By:

(Logo)

Transformer # ZM046199
(925.1201) (325001)
REF. B4316199
(date code)

