

DATA SHEET FOR
TRANSFORMER # 925.1202

Made for STANDARD

<u>LEADS</u>		<u>SCHEMATIC</u>				<u>LEADS</u>	
S#12/12"	0V	WHITE		BROWN	0V	S#12/12"	
S#12/12"	100V	BLUE		A/R THERMAL FUSE 120°C			
S#12/12"	120V	YELLOW		120V RMS / 1250VA	RED	UO = 123.3V RMS	S#12/12"
S#12/12"	0V	ORANGE		A/R THERMAL FUSE 120°C			
S#12/12"	100V	RED		120V RMS / 1250VA	ORANGE	UO = 123.3V RMS	S#12/12"
S#12/12"	120V	BLACK		STATIC SHIELD	YELLOW	120V RMS / 1250VA	S#12/12"
				VIOLET		S#18/12"	

PRIMARIES ARE INSIDE A SLEEVE.
Primaries must be connected together in series or in parallel.
 LEADS: S=Multistranded Lead wire. Length tolerance: +/- 1/2".
 Manufacturing tolerance is +/- 3%.

NOMINAL SUPPLY: 100/120/220/240V +/-10%
 RATED PRIMARY CURRENT: 26/22/13/12/11A
 RATED FREQUENCY: 50/60 Hz
 TEMP. RISE AT RATED LOAD: 60°C

DIMENSIONS/WEIGHT:
 OD = 11.0"
 H = 4.0"
 WEIGHT = 38.5 LBS.

MOUNTING:
 SPECIFIED BY CUSTOMER

CORE DATA:
 CORE # 902326
 NO-LOAD LOSS = 10.2 W
 NO-LOAD AMPS = 87 mA

Dimensions stated above are nominal. Tolerance is 10%.

OTHER SPECIFICATIONS: Transformer is UL recognized to UL544 and UL 2601-1. CSA certified to CSA C22.2 No. 66 and TUV certified to EN60601 and EN60742. CE compliance. Class B insulation. Leakage current < 50µA.

Label: Transformer # ZM843355
 (325002) (925.1202)
 REF. B4313355
 (date code)

SPEC DATE: 06/15/05

By: (Logo)