

DATA SHEET FOR
TRANSFORMER # 930.1202

Made for STANDARD

<u>LEADS</u>		<u>SCHEMATIC</u>				<u>LEADS</u>	
S#12/8"	0V	WHITE		BROWN	0V	S#12/8"	
S#12/8"	100V	BLUE			A/R THERMAL FUSE 120°C		
S#12/8"	120V	YELLOW			RED	UO = 122.2V RMS	S#12/8"
S#12/8"	0V	ORANGE			ORANGE	120V RMS / 1500VA	
S#12/8"	100V	RED			A/R THERMAL FUSE 120°C	UO = 122.2V RMS	S#12/8"
S#12/8"	120V	BLACK			YELLOW	120V RMS / 1500VA	S#12/8"
				VIOLET	STATIC SHIELD	S#18/8"	

PRIMARIES ARE INSIDE A SLEEVE.
Primaries must be connected together in series or in parallel.
 LEADS: S=Multistranded Lead wire. Length tolerance: +/- 1/2".
 Manufacturing tolerance is +/- 3%.

NOMINAL SUPPLY: 100/120/220/240V +/-10%
 RATED PRIMARY CURRENT: 31/26/16/15/13A
 RATED FREQUENCY: 50/60 Hz
 TEMP. RISE AT RATED LOAD: 54°C

DIMENSIONS/WEIGHT:
 OD = 11.0"
 H = 4.5"
 WEIGHT = 50.0 LBS.

MOUNTING:
 SPECIFIED BY CUSTOMER

CORE DATA:
 CORE # 902906
 NO-LOAD LOSS = 13.3 W
 NO-LOAD AMPS = 112 mA

Dimensions stated above are nominal. Tolerance is 10%.

OTHER SPECIFICATIONS: Transformer is UL recognized to UL544 and UL 2601-1. CSA certified to CSA C22.2 No. 66 and TUV certified to EN60601 and EN60742. CE compliance. Class B insulation. Leakage current < 50µA.

Label: Transformer # ZM843356
 (330002) (930.1202)
 REF. B4313356
 (date code)

SPEC DATE: 06/15/05

By: (Logo)