

DATA SHEET FOR

TRANSFORMER # 602.082

Made for STANDARD

page 1 of 1

<u>LEADS</u>	<u>SCHEMATIC</u>	<u>LEADS</u>
S#22/8" 0V WHITE		M#24/8"
S#22/8" 117V WHITE		UO = 11.2V RMS 8.5V RMS / 1.41A RMS
		UO = 11.2V RMS 8.5V RMS / 1.41A RMS

PRIMARIES ARE INSIDE A SLEEVE.

LEADS: S=Multistranded Lead wire. M=Magnet wire self-leads. Length tolerance: +/-1/2".
Manufacturing tolerance is +/- 3%.

NOMINAL SUPPLY: 117V +/-10%
RATED PRIMARY CURRENT: 0.3A

RATED FREQ.: 60 Hz
TEMP RISE AT RATED LOAD = 70 C

DIMENSIONS/WEIGHT:
OD = 2.4"
H = 1.2"
WEIGHT = 0.7 LBS.

MOUNTING:
WASHER/PADS = 50 mm
THICKNESS = 0.04"
HOLE DIAMETER = 0.17"

CORE DATA:
CORE # 15
NO-LOAD LOSS = 0.2 W
NO-LOAD AMPS = 4 mA

Dimensions stated above are nominal. Tolerance is 10%

OTHER SPECIFICATIONS: Transformer is UL recognized to UL 1411 and CSA certified to CSA C22.2 No. 66.

	Label:	
SPEC DATE: 8/14/96	(LOGO)	Transformer # 602.082 (100242) Prim. 117V 60 Hz bk+(wh-wh) Sec. 2x8.5V/1.41A br-re/or-ye (date code)
BY:		