

# DATA SHEET FOR

## TRANSFORMER # 604.122

Made for STANDARD

page 1 of 1

<u>LEADS</u>	<u>SCHEMATIC</u>	<u>LEADS</u>	
S#22/8"      0V      WHITE		M#21/8"	
S#22/8"      117V      WHITE		BROWN      0V UO = 14.6V RMS RED            12V RMS / 1.75A RMS	M#21/8"
		ORANGE      0V UO = 14.6V RMS YELLOW       12V RMS / 1.75A RMS	M#21/8"
			M#21/8"

PRIMARIES ARE INSIDE A SLEEVE.

LEADS: S=Multistranded Lead wire. M=Magnet wire self-leads. Length tolerance: +/-1/2".  
 Manufacturing tolerance is +/- 3%.

NOMINAL SUPPLY:            117V +/-10%  
 RATED PRIMARY CURRENT: 0.4A

RATED FREQ.: 60 Hz  
 TEMP RISE AT RATED LOAD = 60 C

DIMENSIONS/WEIGHT:  
 OD = 2.8"  
 H = 1.3"  
 WEIGHT = 1.1 LBS.

MOUNTING:  
 WASHER/PADS = 50 mm  
 THICKNESS = 0.04"  
 HOLE DIAMETER = 0.17"

CORE DATA:  
 CORE # 30  
 NO-LOAD LOSS = 0.2 W  
 NO-LOAD AMPS = 5 mA

Dimensions stated above are nominal. Tolerance is 10%

OTHER SPECIFICATIONS: Transformer is UL recognized to UL 1411 and CSA certified to CSA C22.2 No. 66.

	Label:	
SPEC DATE:    3/05/96	(LOGO)	Transformer # 604.122 (100422) Prim. 117V 60 Hz bk+(wh-wh) Sec. 2x12V/1.75A br-re/or-ye (date code)
BY:		