

DATA SHEET FOR

TRANSFORMER # 617.182

Made for STANDARD

page 1 of 1

<u>LEADS</u>	<u>SCHEMATIC</u>	<u>LEADS</u>
M#20/8" 0V WHITE		M#17/8"
M#20/8" 117V WHITE		M#17/8"
		M#17/8"
		M#17/8"

PRIMARIES ARE INSIDE A SLEEVE.
 Secondary windings may be connected in series or in parallel.
 LEADS: M=Magnet wire self-leads. Length tolerance: +/- 1/2".
 Manufacturing tolerance is +/- 3%.

NOMINAL SUPPLY: 117V +/-10%	RATED FREQ.: 60 Hz
RATED PRIMARY CURRENT: 1.7A	TEMP RISE AT RATED LOAD = 65 C

<u>DIMENSIONS/WEIGHT:</u>	<u>MOUNTING:</u>	<u>CORE DATA:</u>
OD = 3.9"	WASHER/PADS = 70 mm	CORE # 900140
H = 1.9"	THICKNESS = 0.05"	NO-LOAD LOSS = 0.9 W
WEIGHT = 3.0 LBS.	HOLE DIAMETER = 0.25"	NO-LOAD AMPS = 21 mA

Dimensions stated above are nominal. Tolerance is 10%

OTHER SPECIFICATIONS: Transformer is UL recognized to UL 1411 and CSA certified to CSA C22.2 No. 66.

SPEC DATE: 8/5/96	Label:	
	(LOGO)	Transformer # 617.182 (101742)
BY: _____		Prim. 117V 60 Hz bk+(wh-wh)
		Sec. 2x18V/4.83A br-re/or-ye
		(date code)