

DATA SHEET FOR
TRANSFORMER # ZA84501


Made for STANDARD

page 1 of 1

LEADS

SCHEMATIC

LEADS

S#22/8"	0V	WHITE		BROWN	0V		M#20/8"
S#22/8"	117V	WHITE		BROWN		UO = 13.8V RMS 11.8V RMS / 20VA	M#20/8"

PRIMARIES ARE INSIDE A SLEEVE.

LEADS: S=Multistranded wire. M=Magnet wire self-leads. Length tolerance: +/- 1/2".
Manufacturing tolerance is +/- 3%.

NOMINAL SUPPLY: 117V +/-10%
RATED PRIMARY CURRENT: 0.2A
RATED FREQUENCY: 60 Hz
TEMP. RISE AT RATED LOAD: 24 °C

DIMENSIONS/WEIGHT:

OD = 2.8"
H = 1.4"
WEIGHT = 0.9 LBS.

MOUNTING:

WASHER/PADS = 50mm
THICKNESS = 0.04"
HOLE DIAMETER = 0.17"

CORE DATA:

CORE # 30
CORE LOSS = 0.24 W
NO-LOAD CURRENT = 5 mA

Dimensions stated above are nominal. Tolerance is 10%.

OTHER SPECIFICATIONS: Transformer is UL recognized to UL 1411.

Label:

SPEC DATE: 06/17/05

By:

(Logo)

Transformer # ZA84501
Prim. 117V 60Hz bk+(wh-wh)
Sec. 11.8V/1.70A br-br
(date code)