

DATA SHEET FOR  
TRANSFORMER # ZA84502


Made for STANDARD

page 1 of 1

LEADS

SCHEMATIC

LEADS

M#25/8"	0V	WHITE		BROWN	0V	M#17/8"
					UO = 13.2V RMS	
M#25/8"	117V	WHITE		BROWN	11.8V RMS / 50VA	M#17/8"

PRIMARIES ARE INSIDE A SLEEVE.  
 LEADS: M=Magnet wire self-leads. Length tolerance: +/- 1/2".  
 Manufacturing tolerance is +/- 3%.

NOMINAL SUPPLY: 117V +/-10%  
 RATED PRIMARY CURRENT: 0.48A  
 RATED FREQUENCY: 60 Hz  
 TEMP. RISE AT RATED LOAD: 26 °C

DIMENSIONS/WEIGHT:

OD = 3.8"  
 H = 1.4"  
 WEIGHT = 1.8 LBS.

MOUNTING:

WASHER/PADS = 70mm  
 THICKNESS = 0.05"  
 HOLE DIAMETER = 0.24"

CORE DATA:

CORE # 900095  
 CORE LOSS = 0.6 W  
 NO-LOAD CURRENT = 11 mA

Dimensions stated above are nominal. Tolerance is 10%.

OTHER SPECIFICATIONS: Transformer is UL recognized to UL 1411.

Label:

Transformer # ZA84502  
 Prim. 117V 60Hz bk+(wh-wh)  
 Sec. 11.8V/4.24A br-br  
 (date code)

SPEC DATE: 06/17/05

By:

(Logo)