

DATA SHEET FOR
TRANSFORMER # ZA84503


Made for STANDARD

page 1 of 1

LEADS

SCHEMATIC

LEADS

M#24/8"	0V	WHITE		BROWN	0V		M#15/8"
M#24/8"	117V	WHITE		BROWN		UO = 13.4V RMS 11.8V RMS / 75VA	M#15/8"

PRIMARIES ARE INSIDE A SLEEVE.
LEADS: M=Magnet wire self-leads. Length tolerance: +/- 1/2".
Manufacturing tolerance is +/- 3%.

NOMINAL SUPPLY: 117V +/-10%
RATED PRIMARY CURRENT: 0.73A
RATED FREQUENCY: 60 Hz
TEMP. RISE AT RATED LOAD: 41 °C

DIMENSIONS/WEIGHT:

OD = 3.8"
H = 1.5"
WEIGHT = 2.1 LBS.

MOUNTING:

WASHER/PADS = 70mm
THICKNESS = 0.05"
HOLE DIAMETER = 0.24"

CORE DATA:

CORE # 900095
CORE LOSS = 0.6 W
NO-LOAD CURRENT = 11 mA

Dimensions stated above are nominal. Tolerance is 10%.

OTHER SPECIFICATIONS: Transformer is UL recognized to UL 1411.

Label:

SPEC DATE: 06/17/05

By:

(Logo)

Transformer # ZA84503
Prim. 117V 60Hz bk+(wh-wh)
Sec. 11.8V/6.36A br-br
(date code)