


DATA SHEET FOR
TRANSFORMER # ZA84504

Made for STANDARD

page 1 of 1

<u>LEADS</u>	<u>SCHEMATIC</u>	<u>LEADS</u>
M#22/8" 0V WHITE		BROWN 0V M#14/8"
M#22/8" 117V WHITE		UO = 13.1V RMS 11.8V RMS / 100VA M#14/8"

PRIMARIES ARE INSIDE A SLEEVE.
LEADS: M=Magnet wire self-leads. Length tolerance: +/- 1/2".
Manufacturing tolerance is +/- 3%.

NOMINAL SUPPLY: 117V +/-10%
RATED PRIMARY CURRENT: 0.95A
RATED FREQUENCY: 60 Hz
TEMP. RISE AT RATED LOAD: 40 °C

<u>DIMENSIONS/WEIGHT:</u> OD = 3.8" H = 1.8" WEIGHT = 2.8 LBS.	<u>MOUNTING:</u> WASHER/PADS = 70mm THICKNESS = 0.05" HOLE DIAMETER = 0.24"	<u>CORE DATA:</u> CORE # 900140 CORE LOSS = 0.9 W NO-LOAD CURRENT = 17 mA
---	--	--

Dimensions stated above are nominal. Tolerance is 10%.

OTHER SPECIFICATIONS: Transformer is UL recognized to UL 1411.

SPEC DATE: 06/17/05	Label:	Transformer # ZA84504
		Prim. 117V 60Hz bk+(wh-wh)
By:	(Logo)	Sec. 11.8V/8.47A br-br
		(date code)