DATA SHEET FOR

TRANSFORMER # ZA84505

Made for STANDARD

LEADS			SCHEMATIC			LEADS
M#21/8"	0V	WHITE		BROWN	0V	M#13/8"
					UO = 13.0V RMS	
M#21/8"	117V	WHITE		BROWN	11.8V RMS / 120VA	M#13/8"

PRIMARIES ARE INSIDE A SLEEVE.
LEADS: M=Magnet wire self-leads. Length tolerance: +/- 1/2".
Manufacturing tolerance is +/- 3%.

NOMINAL SUPPLY: 117V +/-10%
RATED PRIMARY CURRENT: 1.14A
RATED FREQUENCY: 60 Hz
TEMP. RISE AT RATED LOAD: 46 °C

DIMENSIONS/WEIGHT:	MOUNTING:	CORE DATA:
OD = 3.9"	WASHER/PADS = 70mm	CORE # 900140
H = 2.0"	THICKNESS = 0.05"	CORE LOSS = 0.9 W
WEIGHT = 3.0 LBS.	HOLE DIAMETER = 0.24"	NO-LOAD CURRENT = 17 mA

Dimensions stated above are nominal. Tolerance is 10%.

OTHER SPECIFICATIONS: Transformer is UL recognized to UL 1411.

Label:

Transformer # ZA84505
Prim. 117V 60Hz bk+(wh-wh)
Sec. 11.8V/10.17A br-br
(date code)

SPEC DATE: 06/17/05

(Logo)

By: