

DATA SHEET FOR  
TRANSFORMER # ZA84708


Made for STANDARD

page 1 of 1

LEADS

SCHEMATIC

LEADS

M#15/8"	0V	WHITE		BROWN	0V		
					UO = 12.5V RMS		
M#15/8"	117V	WHITE		BROWN	11.8V RMS / 500VA		S#6/8"

PRIMARIES ARE INSIDE A SLEEVE.  
LEADS: S=Multistranded wire. M=Magnet wire self-leads. Length tolerance: +/- 1/2".  
Manufacturing tolerance is +/- 3%.

NOMINAL SUPPLY: 117V +/-10%  
RATED PRIMARY CURRENT: 4.5A  
RATED FREQUENCY: 60 Hz  
TEMP. RISE AT RATED LOAD: 53 °C

DIMENSIONS/WEIGHT:

OD = 5.3"  
H = 3.0"  
WEIGHT = 9.0 LBS.

MOUNTING:

WASHER/PADS = 110mm  
THICKNESS = 0.08"  
HOLE DIAMETER = 0.32"

CORE DATA:

CORE # 900508  
CORE LOSS = 2.6 W  
NO-LOAD CURRENT = 49 mA

Dimensions stated above are nominal. Tolerance is 10%.

OTHER SPECIFICATIONS: Transformer is UL recognized to UL 1411.

Label:

Transformer # ZA84708  
Prim. 117V 60Hz bk+(wh-wh)  
Sec. 11.8V/42.38A br-br  
(date code)

SPEC DATE: 06/17/05

By:

(Logo)