

DATA SHEET FOR
TRANSFORMER # ZA84709

Made for STANDARD

page 1 of 1

LEADS

SCHEMATIC

LEADS

M#21/8"	0V	white	┌───┐		┌───┐	brown	0V		S#12/8"
							(UO = 13.0V rms)		
M#21/8"	117V	white	┌───┐		┌───┐	brown	11.8V rms / 150 VA		S#12/8"

PRIMARIES ARE INSIDE A SLEEVE.
LEADS: S=Multistranded lead wire. M=Magnet wire self-leads.
Length tolerance: +/- 1/4". Manufacturing tolerance is +/- 3%.

NOMINAL SUPPLY: 117V +/- 10%	RATED FREQ.: 60 Hz
RATED PRIMARY CURRENT: 1.42 A	TEMP RISE AT RATED LOAD = 54 °C

<u>DIMENSIONS/WEIGHT:</u>	<u>MOUNTING:</u>	<u>CORE DATA:</u>
OD = 3.9 "	WASHER/PADS = 2.8"/70mm	CORE # 900159
H = 2.4 "	THICKNESS = .05 "	NO-LOAD LOSS = 1 W
WEIGHT = 3.3 lbs.	HOLE DIAMETER = .24 "	NO-LOAD AMPS = 19 mA

Dimensions stated above are nominal. Tolerance is 10%

OTHER SPECIFICATIONS: Transformer is UL recognized to UL 1411.

	┌───┐	Label:	┌───┐
		Transformer # ZA84709	
		Prim. 117V 60Hz bk+(wh-wh)	
		Sec. 11.8V/500W br-br	
		date code)	
SPEC DATE: 3/28/96	(LOGO)		
BY: _____	┌───┐		┌───┐

DATA SHEET FOR
TRANSFORMER # ZA84709

Made for STANDARD

page 1 of 1

LEADS

SCHEMATIC

LEADS

M#21/8"	0V	white	┌───┐		┌───┐	brown	0V		S#12/8"
							(UO = 13.0V rms)		
M#21/8"	117V	white	┌───┐		┌───┐	brown	11.8V rms / 150 VA		S#12/8"

PRIMARIES ARE INSIDE A SLEEVE.
LEADS: S=Multistranded lead wire. M=Magnet wire self-leads.
Length tolerance: +/- 1/4". Manufacturing tolerance is +/- 3%.

NOMINAL SUPPLY: 117V +/- 10%	RATED FREQ.: 60 Hz
RATED PRIMARY CURRENT: 1.42 A	TEMP RISE AT RATED LOAD = 54 °C

<u>DIMENSIONS/WEIGHT:</u>	<u>MOUNTING:</u>	<u>CORE DATA:</u>
OD = 3.9 "	WASHER/PADS = 2.8"/70mm	CORE # 900159
H = 2.4 "	THICKNESS = .05 "	NO-LOAD LOSS = 1 W
WEIGHT = 3.3 lbs.	HOLE DIAMETER = .24 "	NO-LOAD AMPS = 19 mA

Dimensions stated above are nominal. Tolerance is 10%

OTHER SPECIFICATIONS: Transformer is UL recognized to UL 1411.

	┌───┐	Label:	┌───┐
		Transformer # ZA84709	
		Prim. 117V 60Hz bk+(wh-wh)	
		Sec. 11.8V/500W br-br	
		date code)	
SPEC DATE: 3/28/96	(LOGO)		
BY: _____	┌───┐		┌───┐